

Product Datasheet

10-port Gigabit Uplink Smart PoE Switch

(GWS-H1108PGEBS)



OVERVIEW

The GWS-H1108PGEBS is a smart PoE switch. It has 8*10/100M RJ45 ports and 2*10/100/1000M uplink RJ45 ports. Port 1-8 can support IEEE 802.3 af/at PoE standard and single-port PoE power up to 30W. PoE port can support the watchdog servo function. When the port communication fails, the corresponding port PoE will automatically restart and restore network communication. PoE power supply has a delayed start function. The port power supply is turned on in sequence (within 2 seconds) to prevent the load from starting up with excessive current, and the power supply causes power overload protection. As a PoE power supply device, it can automatically detect and identify the power-receiving device that meets the standard and power it through the network cable. It can power wireless AP, IP camera, network phone, video access control intercom, and other PoE terminal devices through the network cable to meet the network environment that requires a high-density PoE power supply. It is suitable for small and

medium-sized enterprises such as hotels, campuses, parks, banks, hospitals, and factories to build economical and efficient networks. Unmanaged mode, plug and play, no configuration, simple and convenient to use.

FEATURE

■ 10/100M fast Ethernet access

- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.
- ◇ Provide 8*10/100Base-TX RJ45 ports and 2*10/100/1000Base-T RJ45 ports to enable users to flexibly network to meet the networking needs of various scenarios.

■ Smart PoE power supply

- ◇ 8*10/100Base-TX RJ45 ports support PoE power to meet the needs of PoE power in various scenarios in the security field.
- ◇ Comply with IEEE 802.3 af/at PoE standard, automatically identify PoE devices for power supply, and not damage non-PoE devices.
- ◇ PoE port can support the watchdog function, which can automatically detect the data communication status in real time. When the port load crashes, the corresponding port PoE will automatically restart and repair the network communication.
- ◇ PoE port has a delayed startup function. The ports start completely within 2 seconds from left to right (the first port) to prevent the instantaneous unified power supply from causing instantaneous overload and power overload protection. It effectively solves the problem of power overload protection caused by capacitive load or large power required at startup.

■ Stable and reliable


- ◇ Plug and play, no configuration, easy to use and maintain.
- ◇ The user-friendly panel can show the device status through the LED indicator of P and Link.
- ◇ Low power consumption, no fan, plastic housing, ventilation holes on the side, and excellent heat dissipation to ensure stable operation of the switch.

TECHNICAL SPECIFICATION

Model	GWS-H1108PGEBS
Interface Characteristics	
Fixed Port	8*10/100Base-TX PoE ports (Data /Power) 2*10/100/1000Base-T uplink RJ45 ports (Data)
Ethernet Port	Port 1-8 can support 10/100Base-TX and port 9-10 can support 10/100/1000Base-T auto-sensing, full/ half duplex MDI/ MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤ 100 meters) 100BASE-TX: Cat5 or later UTP (≤ 100 meters) 1000BASE-T: Cat5e or later UTP (≤ 100 meters)
Chip Parameter	
Network Protocol	IEEE 802.3 10BASE-T, IEEE 802.3i 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3x
Forwarding Mode	Store and Forward(Full wire speed)
Switching Capacity	10Gbps (non-blocking)
Forwarding Rate@64byte	4.17Mpps
MAC	2K
Buffer Memory	1M
Jumbo Frame	16K
LED Indicator	Power: PWR (Green), Network: Link (Green)
PoE& Power Supply	
PoE Port	Port 1-8
Power Supply Pin	1/2(+) 3/6(-)
Max Power Per Port	30W, IEEE 802.3 af/at
Total PWR/ Input Voltage	100W/ (AC100-240V)
Power Consumption	Standby<6W, full load<100W
Power Supply	Built-in power supply, AC100-240V 50-60Hz, 2.0A
Physical Parameter	

Operation Temp/ Humidity	-20~+50°C, 5%~90% RH non condensing
Storage Temp/ Humidity	-40~+75°C, 5%~95% RH non condensing
Dimension (L*W*H)	166*86*44.5mm
Net /Gross Weight	0.38kg/ 0.42kg
Installation	Desktop, Wall mount
Certification& Warranty	
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30
Warranty	1 year, lifelong maintenance.

DIMENSION



ORDERING INFORMATION

Model	Description	Built-in Power Supply
GWS-H1108PGEBS	Smart PoE switch with 8*10/100M RJ45 ports and 2*10/100/1000M RJ45 ports. Port 1-8 can support IEEE 802.3 af/at PoE standard. It has watchdog function and delayed start function. Built-in power supply.	100W

PACKING LIST

Packing List	Content	Qty	Unit
	10-port Gigabit uplink smart PoE switch	1	Set
	AC Power Cable	1	PC
	User Guide	1	PC
	Warranty Card and Certificate of Conformity	1	PC

CONTACT US



Tel: 0086-752-3397806

WeChat: HZGWS--PoE

Email: hkgws@hkgws.com

Skype: [hkgws@hkgws.com](https://www.skype.com/people/hkgws@hkgws.com)

Website: www.hkgws.com



Address: Building 3, Phase II, Xinghe Artificial Intelligence Industrial Park, No.333 Zhongkai 6th Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou